

KDS KDS Frame fixing with long expansion zone - countersunk pozidrive (cont.)

Products in standard packaging									
Index	Plug		Bit	Screw		Fixture Max thickness	Quantity		
	Diameter	Length		Diameter	Length		Box	Outer	Pallet
	mm						pcs		
KDS-10120	10	120	PZ3	6,8	125	60	25	400	9600
KDS-10140	10	140	PZ3	6,8	145	80	25	300	7200
KDS-10160	10	160	PZ3	6,8	165	100	25	300	7200
KDS-10200	10	200	PZ3	6,8	205	140	25	200	4800
KDS-10240	10	240	PZ3	6,8	245	180	25	200	4800

Products in the gravity fed display box									
Index	Plug		Bit	Screw		Fixture Max thickness	Quantity		
	Diameter	Length		Diameter	Length		Box	Outer	Pallet
	mm						pcs		
K-P3-KDS-08100	8	100	PZ3	4,9	105		150*	150*	8100
K-P3-KDS-08120	8	120	PZ3	4,9	125	60	100*	100*	5400
K-P3-KDS-08140	8	140	PZ3	4,9	135	800	120*	120*	6480
K-P3-KDS-10080	10	80	PZ3	6,8	85	20	100*	100*	5400
K-P3-KDS-10100	10	100	PZ3	6,8	105	40	120*	120*	6480
K-P3-KDS-10120	10	120	PZ3	6,8	125	60	100*	100*	5400
K-P3-KDS-10140	10	140	PZ3	6,8	145	80	80*	80*	4320
K-P3-KDS-10160	10	160	PZ3	6,8	165	100	60*	60*	3240
K-P3-KDS-10200	10	200	PZ3	6,8	205	140	40*	40*	2160
K-P3-KDS-10240	10	240	PZ3	6,8	245	180	40*	40*	2160

* Each product (1pcs) is labelled for retail sale

KKS Frame fixing with short expansion zone - countersunk pozidrive

Frame fixing with short expansion zone for fixing in concrete and solid brick

Approvals and Reports

- AT-15-8987/2012
- AT-15-8987/2012 - Anex nr 1



Features and benefits

- The framework plug with the funnel to veneering with the soft substrates (e.g. Wood)
- The strut plug with a wide range of application
- Durable, high quality PA6 grade nylon plug for extended fixing life
- Rigid nylon sleeve prevents frame distortion during tightening
- Zig-zag design ensures enhanced expansion

Applications

- Door and window frames

Base materials

Approved for use in:

- Concrete
- Solid Brick

Also Suitable for use in:

- Natural stone



KKS Frame fixing with short expansion zone - countersunk pozidrive (cont.)

Products in standard packaging									
Index	Plug		Bit	Screw		Fixture Max thickness	Quantity		
	Diameter	Length		Diameter	Length		Box	Outer	Pallet
	mm						pcs		
KKS-08060	8	60	PZ3	4,9	65	20	100	1200	28800
KKS-08080	8	80	PZ3	4,9	85	40	50	800	19200
KKS-08100	8	100	PZ3	4,9	105	60	50	600	14400
KKS-08120	8	120	PZ3	4,9	125	80	50	600	14400

Products in the gravity fed display box									
Index	Plug		Bit	Screw		Fixture Max thickness	Quantity		
	Diameter	Length		Diameter	Length		Box	Outer	Pallet
	mm						pcs		
K-P3-KKS-08060	8	60	PZ3	4,9	65	20	200*	200*	10800
K-P3-KKS-08080	8	80	PZ3	4,9	85	40	200*	200*	10800
K-P3-KKS-08100	8	100	PZ3	4,9	105	60	150*	150*	8100
K-P3-KKS-08120	8	120	PZ3	4,9	125	80	100*	100*	5400
K-P3-KKS-10100	10	100	PZ3	6,8	105	60	100*	100*	5400
K-P3-KKS-10120	10	120	PZ3	6,8	125	80	100*	100*	5400
K-P3-KKS-10140	10	140	PZ3	6,8	145	100	80*	80*	4320
K-P3-KKS-10160	10	160	PZ3	6,8	165	120	80*	80*	4320

* Each product (1pcs) is labelled for retail sale

KKD Frame fixing with short expansion zone - hex head

Frame fixing with short expansion zone for fixing in concrete and solid brick

Approvals and Reports

- AT-15-8987/2012
- AT-15-8987/2012 - Anex nr 1



Features and benefits

- Plug with the hexagonal screw allows stable mounting of hard materials (e.g. Steel)
- The strut plug with a wide range of application
- Durable, high quality PA6 grade nylon plug for extended fixing life
- Rigid nylon sleeve prevents frame distortion during tightening
- Zig-zag design ensures enhanced expansion

Applications

- Door and window frames

Base materials

Approved for use in:

- Concrete
- Solid Brick

Also Suitable for use in:

- Natural stone

